

AMENDMENT TO THE CLAIMS

Please replace the claims with the following rewritten listing.

1. (Currently Amended) A dental suction apparatus ~~(10)~~ for suctioning fluids and debris from the mouth cavity of a patient during a treatment, said apparatus having a hollow base body (12) with a longitudinal axis X-X that comprises an outer surface (16), an inner surface (14) and a suction port (20), ~~wherein e~~characterized in that a mirrored surface (24) is disposed ~~in the region~~ on the inner surface (14) of the suction port (20) so as to allow viewing that at least parts of the mouth cavity can be viewed through the suction port (20).
2. (Currently Amended) The dental suction apparatus ~~(10)~~ as set forth in claim 1, ~~e~~characterized in that wherein the inner surface (14) has the mirrored surface (24) that is viewable through the suction port (20), said suction port (20) being configured to be at an incline with respect to the longitudinal axis X-X, that the area of the suction port (20) exceeds a cross-sectional area of the base body (12) extending across the longitudinal axis.
3. (Currently Amended) The dental suction apparatus ~~(10)~~ as set forth in claim 1, ~~e~~characterized in that wherein the outer surface (16) of the base body (12) also has a mirroring surface (24).
4. (Currently Amended) The dental suction apparatus ~~(10)~~ as set forth in claim 1, ~~e~~characterized in that wherein the mirroring surface (24) is disposed on a pluggable element that is releasably connected to the suction apparatus.
5. (Currently Amended) The dental suction apparatus ~~(10)~~ as set forth in claim 4, ~~e~~characterized in that wherein a groove for insertion of the pluggable element is disposed in the region of the suction port (20).

6. (Currently Amended) The dental suction apparatus (10) as set forth in claim 1, ~~characterized in that~~ wherein the base body (12) is configured to be deformable in the longitudinal direction in such a manner that the orientation of the longitudinal axis X-X may be varied.
7. (Currently Amended) The dental suction apparatus (10) as set forth in claim 6, ~~characterized in that~~ wherein the base body (12) is made from a flexible plastic material.
8. (Currently Amended) The dental suction apparatus (10) as set forth in claim 6, ~~characterized in that~~ wherein the base body (12) has at least one spherical joint.
9. (Currently Amended) The dental suction apparatus (10) as set forth in claim 1, ~~characterized in that~~ wherein a light source is disposed in the region of the suction port (20) so as to illuminate the region to be reflected.
10. (Currently Amended) A dental suction apparatus (10) for suctioning fluids and debris from the mouth cavity of a patient during a treatment, said apparatus having a hollow base body (12) with a longitudinal axis X-X that comprises an outer surface (16), an inner surface (14) and a suction port (20), ~~characterized in that~~ wherein the base body (12) is configured to be deformable in the longitudinal direction in such a manner that the orientation of the longitudinal axis X-X may be varied.
11. (Currently Amended) The dental suction apparatus (10) as set forth in claim 1, ~~characterized in that~~ wherein the inner surface (14) has the mirrored surface (24) that is viewable through the suction port (20), said suction port (20) being configured to be at an incline with respect to the longitudinal axis X-X, that the area of the suction port (20) exceeds a cross-sectional area of the base body (12)

extending across the longitudinal axis, and further characterized in that the outer surface (16) of the base body (12) also has a mirroring surface (24).

12. (Currently Amended) The dental suction apparatus (10) as set forth in claim 11, ~~characterized in that~~ wherein the mirroring surface (24) is disposed on a pluggable element that is releasably connected to the suction apparatus.
13. (Currently Amended) The dental suction apparatus (10) as set forth in claim 12, ~~characterized in that~~ wherein a groove for insertion of the pluggable element is disposed in the region of the suction port (20).
14. (Currently Amended) The dental suction apparatus (10) as set forth in claim 11, ~~characterized in that~~ wherein the base body (12) is configured to be deformable in the longitudinal direction in such a manner that the orientation of the longitudinal axis X-X may be varied.
15. (Currently Amended) The dental suction apparatus (10) as set forth in claim 11, ~~characterized in that~~ wherein a light source is disposed in the region of the suction port (20) so as to illuminate the region to be reflected.